



GUANGZHOU MATEYS CHEMICALS LTD.

ZN-155S Zinc Sealing Agent

1. Specifications

- (1) Suitable for Zinc and Zinc alloy deposit with passive films
- (2) Uniform, transparent & no Cr6+ deposit
- (3) Transparent organ film with higher corrosion resistance
- (4) 50-120h in NSS with ZN-155S
- (5) Eco agent without Cr mate
- (6) Simple operation
- (7) Low cost
- (8) Remove organic layer if need, with Alkaline cleaner in dipping at around 60 °C

2. Conditions

Conditions	Range	Perfect
Concentration	10 ~ 30%	20%
Temperature	15 ~ 40°C	25°C
pH Value	8.5 ~ 10.0	
Dipping time	10 ~ 40s	15s
Dripping time	1 ~ 3min	2min
Drying temperature	70 ~ 90°C	80°C
Drying time	10 ~ 30min	20min

Remarks. Pls kindly give us an email for more details.

ADD: 25 Jianhua Rd., Tianhe Software Park, Keyun Rd.,

Tianhe Dist., Guangzhou, China510665

TEL: +86 20 85576176/85555261/85555262

CEL: +86 13922181787 Skype: gzmateys

Email: gzmateys@qq.com gzmateys@163.com

URL: www.gzmateys.com/en gzmateys.en.alibaba.com